

EFQ SERIES

COMMERCIAL FAN-FORCED WALL HEATER



IDEAL SPACES

- Offices
- Stores
- Schools
- Churches
- Hospitals
- Dormitories
- Airport Terminals
- Reception Rooms
- Lobbies
- Corridors
- Stariwells
- Conference Rooms
- Hallways
- Waiting Rooms

COLORS

- White

DIMENSIONS

- Grille: 31-3/4" W x 22-3/4" H x 1-1/2" D
- Back Box: 30-1/2" W x 21-1/8" H x 3-3/4" D

TEMP RANGE

- 60°– 90°F

CFM

- 200

- Steel finned metal sheath electric heating elements with low sheath temperatures provided uniform heat and long service life
- Rugged stamped steel front cover provides a down-flow air pattern. Integral thermostat for quick installation; separate thermostat not necessary
- Thermal overheat protectors disconnect power in event of accidental blockage
- Power on/off switch for added safety during maintenance
- Permanently lubricated enclosed fan motor provides long-life and low maintenance



EFQ SERIES**COMMERCIAL FAN-FORCED WALL HEATER****MODELS & SPECIFICATIONS**

CATALOG NO.	UPC	VOLTS	PHASE	WATTS	AMPS	BUILT-IN THERMOSTAT	SHIP WT. (LBS.)
EFQ6008	6 85360 02135 5	208	1	6000	28.8	Yes	50
EFQ60048	6 8536 02132 4	480	1	6000	12.5	Yes	50
EFQ6006	6 8536 02133 1	600	1	6000	10	Yes	50
EFQ8008	6 8536 02141 6	208	1	8000	38.5	Yes	50
EFQ8004	6 8536 02137 9	240	1	8000	33.3	Yes	50
EFQ8003	6 8536 02136 2	347	1	8000	23.1	Yes	50
EFQ80048	6 8536 02138 6	480	1	8000	16.7	Yes	50
EFQ8006	6 8536 02139 3	600	1	8000	13.3	Yes	50

ACCESSORIES

CATALOG NO.	UPC	DESCRIPTION	SHIP WT. (LBS)
EFQSM	6 85360 02127 0	Surface Mounting Frame	6
EFQS1	6 85360 02128 7	1 in. Semi-Recess Frame	5
EFQS2	6 85360 02129 4	2 in. Semi-Recess Frame	6
EFQR24	6 85360 02126 3	24V Power Relay	1
EFQR120	6 85360 02125 6	120V Power Relay	1