

MWUH SERIES

HORIZONTAL/DOWNFLOW UNIT HEATER



IDEAL SPACES

- Factories
- Garages
- Maintenance Rooms
- Warehouses
- Public Buildings
- Service Stations
- Workshops
- Stairwells

COLORS

- Neutral Gray

DIMENSIONS

- 14"L x 12-1/2"H x 11-1/4"D

TEMP RANGE

- 45°–90°F

CFM

- 270



- Heater comes equipped with ceiling-mount bracket for horizontal or vertical flow mounting or any position in between
- Built-in single-pole thermostat
- Copper-brazed steel fins with steel sheathed tubular elements for uniform heating and longevity
- Adjustable louvers control air throw direction
- Automatic fan delay eliminates cold drafts on start-up and discharges residual heat from the heater body during shut down
- High limit cut-off with visual alarm automatically shuts off current in event of overheating and reactivates unit when temperature returns to normal
- Disconnect switch (DS30) option available for heaters 24 amps or lower.



MWUH SERIES

HORIZONTAL/DOWNFLOW UNIT HEATER

MODELS & SPECIFICATIONS

CATALOG NO.	UPC	VOLTS	WATTS	BTU/HR	FAN MOTOR WATTS	CONTROL & FAN MOTOR VOLTS	FAN MOTOR RPM	AIR THROW (FT.)	MIN. MOUNTING HEIGHT (FT.)	HEATER AMPS	MIN. CKR. AMPS	SHIP WT. (LBS.)
MWUH5004	6 85360 03880 3	208	1874	6396	6	208	1350	16	6	9.0	11.3	24
			2500	8553						12.0	15.0	
			2812	10659						15.0	18.5	
			3750	12799						18.0	22.5	
		240	2500	8533		10.4				13.0		
			3332	11365		13.9				17.4		
			3750	14215		17.4				21.8		
			5000	17065		20.9				26.1		
MWUH7504	6 85360 14870 0	208	2812	9598	6	208	1400	18	8	13.5	11.3	27
			3750	12799						18.0	15.0	
			4685	15990						22.5	18.5	
			5625	19198						27.1	22.5	
		240	3750	12799		15.6				19.5		
			5000	17065		20.8				26.0		
			6250	21331		26.0				32.5		
			7500	25598		31.3				39.1		
MWUH5008	6 85360 04771 3	208	2500	8533	6	208	1400	16	8	12.0	-	26
			3332	11365						16.0	15.0	
			4165	14215						20.0	20.0	
			5000	17065						24.0	26.0	

NOTE: Disconnect switch (DS30) option available for heaters 24 amps or lower. Optional CWB1A combination wall/ceiling bracket available.

