



INDUSTRIAL OSCILLATING AIR CIRCULATOR



30ACHO shown with optional 2430PB pole and base.



- Oscillates in 90° arc or can be locked in fixed position
- Available in two styles:
 - Assembled head (motor-blade-guard) in one UPS-able carton optional mount in separate UPS-able carton.
 - Unassembled uni-pack all components (motor, blade, guards and mount) in one UPS-able carton.
- Not to be used with: I-Beam Mount (2430I), Ceiling Mount (2430C), Suspension Mount (2430S)

Fan Performance

Blade Size	Fan Head	Max Amps	CFM	
			High	Low
24"	24ACHO	2.2	7,000	5,900
30"	30ACHO	2.5	8,200	6,200

Motor	2-speed 1/4 HP 1Ø 115 volt ball bearing totally enclosed permanently lubricated permanent split capacitor
Switch	Pull chain
Cord	12' long 3 conductor SJT type
Blade	30" unit - 3 Blade - Coated Steel 24" unit - 3 Blade - Coated Steel
Guard	Double locking powder coat finish
Fan Head Tilt	pedestal - 10° down or up wall mount - 10° down or up
Column Adjustment	48-7/8 to 60 inches
Pedestal base	27" diameter steel dome
Column/Base Connect	5 carriage bolts

Meets OSHA standards / 1 year limited warranty

MEP recommends the use of safety cable model 2430SC with this fan when mounted on a wall mount bracket.

Ordering Summary

BLADE SIZE	FAN TYPE	ORDER NUMBER		SHIPPING WEIGHT	
		FAN HEAD	MOUNT	HEAD	MOUNT
24"	Head	24ACHO	—	40 lbs.	—
24"	Pedestal	24ACHO	2430PB	40 lbs.	35 lbs.
24"	Wall Mount	24ACHO	2430WG	40 lbs.	5 lbs.
30"	Head	30ACHO	—	47 lbs.	—
30"	Pedestal	30ACHO	2430PB	47 lbs.	35 lbs.
30"	Wall Mount	30ACHO	2430WG	47 lbs.	5 lbs.

Unassembled Uni-pack Ordering Summary

BLADE SIZE	FAN TYPE	UNIPACK ORDER#	SHIPPING WEIGHT
24"	Pedestal Fan	24ACPOU	73 lbs.
24"	Wall Mount Fan	24ACWOU	42 lbs.
30"	Pedestal Fan	30ACPOU	78 lbs.
30"	Wall Mount	30ACWOU	47 lbs.

Optional Accessories

TYPE	ORDER NUMBER
Wheel Kit	PBWK
Safety Cable	2430SC