



SAFETY YELLOW HIGH PERFORMANCE AIR CIRCULATOR



AF30H fan head shown with optional **2430PBY** (pole and base) and **PBWK** (wheel kit).



- Safety yellow motor, guards, and mounts
- Hinged guards swing open for easy cleaning
- Factory assembled motor - blade - guard assembly to ease final assembly
- 6' drop cord extension available

Fan Performance

Blade Size	Fan Head	Max Amps	CFM	
			High	Low
30"	AF30H	2.9	10,800	7,700

Motor	2-speed 1/3 HP 1Ø 120 volt totally enclosed permanently lubricated permanent split capacitor ball bearing motor
Switch	2-speed, Drop-Cord switch
Cord	12' long 3 conductor SJT type
Blade	Coated steel
Guard	3-1/2" oversized double hinged locking, Yellow Powder coated
Fan Head Tilt	Pedestal - 10° down or 28° up Wall mount - 40° down or 0° up
Column Adjustment	48-7/8 to 66 inches
Pedestal base	27" diameter steel dome
Column/Base Connect	5 carriage bolts

Meets OSHA standards.

MEP recommends the use of safety cable model 2430SC with this fan when mounted on a wall, I-beam, ceiling, or adapter mount.

Ordering Summary

BLADE SIZE	FAN TYPE	ORDER NUMBER		SHIPPING WEIGHT	
		FAN HEAD	MOUNT	HEAD	MOUNT
30"	Head	AF30H	—	69 lbs.	—
30"	Pedestal	AF30H	2430PBY	69 lbs.	37 lbs.
30"	Wall Mount	AF30H	2430WY	69 lbs.	5 lbs.
30"	I-Beam Mount	AF30H	2430IY	69 lbs.	7 lbs.
30"	Ceiling Mount	AF30H	2430CY	69 lbs.	4 lbs.

Optional Accessories

TYPE	ORDER NUMBER
Drop Cord Extension-6'	DCE6
Motor with Drop Cord Switch	1010MPDCS
Guard & Blade Set - Hinged	AF30GB
Wheel Kit	PBWK
Safety Cable	2430SC