


“SECONDARY SUPPORT” CABLE Now Standard Equipment on all models.

This new “Secondary Support” cable complies with existing CSA (Canadian Standards Association) requirements and all other proposed safety regulations for overhead air movement equipment.

EXCLUSIVE SHAFT CONNECTION

By attaching directly from the beam to the permanent motor shaft this “Secondary Support” cable protects against any possible failure or improper installation of the fan J hook, upper yoke assembly, rod, lower yoke assembly and related hardware.



SPECIFICATION FEATURES:

- Pre-Installed directly to permanent shaft for maximum protection and easy installation.
- 6' length of heavy-duty 7x7 1/8" galvanized cable.
- Rated breaking strength of 1700 lbs.
- Galvanized U-bolt wire clips (2) included for attachment to beam structure for extra strength and security.
- CSA (Canadian Standards Association) listed (Standard C22.2 Sept. 1986)

OPTIONAL MOTOR SPEED CONTROLS

Only Leading Edge motor speed controls are custom engineered, manufactured and U.L. listed to all Leading Edge Fans.

- For single and multiple fan installations.
- Dial-on/off switch allows high-to-low variable speed control above factory-set “anti-stall” level of 50 VAC.


Available in 3, 8, 12 Amp Models, 120/220/277 Volt



Models:
12003
22003
27703



Models:
12008
22008
27708



Models:
12012
22012
27712



Model: 12001N
For Single Fan

Model: 12005N
For Two Fans

Models:
12001N
12005N

IMPACT RESISTANT CEILING FAN GUARDS

EXTRA HEAVY-DUTY, TOTALLY ENCLOSED IMPACT RESISTANT CEILING FAN GUARD FOR SCHOOL GYMNASIUMS, INDOOR AREAS, PUBLIC ARENAS, ETC.



MODEL	ITEM	SHIP WT.
28001	FAN GUARD 62" DIAMETER FOR INDUSTRIAL 56" AND 60" FANS ♦	50
28002	FAN GUARD 52" DIAMETER FOR COMMERCIAL 36" AND 48" FAN ONLY ♦	40
9FP024	WHITE TILTED CANOPY COVER - BROWN(9FP023), BLACK(9FP023B)	1
9D12BW	DOWNRODS - 12" } Also available in brown, replace "W" in model	1
9D18BW	DOWNRODS - 18" } number with "B" Ex. 9D36BB	1
9D36BW	DOWNRODS - 36" } (FOR LONGER SIZES - CONSULT FACTORY)	3
9D48BW	DOWNRODS - 48" }	4
99992	OUTDOOR LOCATION INSTALLATION KIT*	1

Custom models available. Consult with factory for information and specifications.

- Use only with heavy-duty / industrial models - Not recommended for low ceiling applications.

♦ Fan Guards ship via UPS

*Only for use with harsh environment fans.