



## LOW-PROFILE SERIES



For use as a *Thermal Barrier* in retail customer entrances, malls, stores, hospitals, post offices, restaurants, concession windows and walk-in coolers.

### FEATURES

- Modern contemporary design with choice of electro-static powder paint or quality stainless steel.
- Cross-flow blower wheels for maximum outlet uniformity
- Easily adjustable air directional vanes.
- Two speed motor with convenient selector switch
- Pre-wired 48 inch molded cord/plug for simple installation.
- Quick-Mount mounting plate included. No Template required to locate mounting screws
- Units can be installed in series for side by side continuous mounting.

### APPLICATION GUIDELINES:

- Create an “open door” atmosphere in retail establishments.
- For mounting heights of 7 ft. for exterior customer entrances or 8 ft. interior doors.
- Reduce infiltration of exterior air, fumes, dust and dirt.
- Act as a temperature separation device, repelling outside air while maintaining interior environment.
- Patented design allows for continuous mounting.

### EXCLUSIVE FEATURES ARCHITECTURAL SERIES:

- Extruded anodized aluminum design that compliments store interiors and public facilities.
- Custom paint to accent architectural sill-height heaters in vestibules and reception areas.

#### Low-Profile - Contemporary Series



#### Low-Profile - Architectural Series



MODEL	NOZZLE WIDTH (IN)	VOLTS	AMPS	MAX VEL FPM	AVG VEL FPM	AIRFLOW CFM	WT. LBS	MOTORS HP
<b>Contemporary Powder Paint</b>								
MLP36001115GR	36	120	1.3	1800	1800 / 1350	1200 / 900	32	1 @ 1/15
MLP42001110GR	42	120	1.6	1800	1800 / 1350	1380 / 1040	37	1 @ 1/10
MLP48001108GR	48	120	2.1	1800	1800 / 1350	1600 / 1210	42	1 @ 1/8
MLP60001108GR	60	120	2.1	1800	1800 / 1350	2060 / 1550	53	1 @ 1/8
MLP36001208GR	36	240	0.7	1800	1800 / 1350	1200 / 900	32	1 @ 1/15
MLP42001208GR	42	240	0.7	1800	1800 / 1350	1380 / 1040	37	1 @ 1/10
MLP48001206GR	48	240	1.0	1800	1800 / 1350	1600 / 1210	42	1 @ 1/8
MLP60001206GR	60	240	1.0	1800	1800 / 1350	2060 / 1550	53	1 @ 1/8
<b>Contemporary Stainless Steel</b>								
MLP36001115GRSS	36	120	1.3	1800	1800 / 1350	1200 / 900	32	1 @ 1/15
MLP42001110GRSS	42	120	1.6	1800	1800 / 1350	1380 / 1040	37	1 @ 1/10
MLP48001108GRSS	48	120	2.1	1800	1800 / 1350	1600 / 1210	42	1 @ 1/8
MLP60001108GRSS	60	120	2.1	1800	1800 / 1350	2060 / 1550	53	1 @ 1/8
MLP36001208GRSS	36	240	0.7	1800	1800 / 1350	1200 / 900	32	1 @ 1/15
MLP42001208GRSS	42	240	0.7	1800	1800 / 1350	1380 / 1040	37	1 @ 1/10
MLP48001206GRSS	48	240	1.0	1800	1800 / 1350	1600 / 1210	42	1 @ 1/8
MLP60001206GRSS	60	240	1.0	1800	1800 / 1350	2060 / 1550	53	1 @ 1/8
<b>Architectural Series</b>								
MLP36001115GA	36	120	1.3	1800	1800 / 1350	1200 / 900	32	1 @ 1/15
MLP42001110GA	42	120	1.6	1800	1800 / 1350	1380 / 1040	37	1 @ 1/10
MLP48001108GA	48	120	2.1	1800	1800 / 1350	1600 / 1210	42	1 @ 1/8
MLP60001108GA	60	120	2.1	1800	1800 / 1350	2060 / 1550	53	1 @ 1/8
MLP36001208GA	36	240	0.7	1800	1800 / 1350	1200 / 900	32	1 @ 1/15
MLP42001208GA	42	240	0.7	1800	1800 / 1350	1380 / 1040	37	1 @ 1/10
MLP48001206GA	48	240	1.0	1800	1800 / 1350	1600 / 1210	42	1 @ 1/8
MLP60001206GA	60	240	1.0	1800	1800 / 1350	2060 / 1550	53	1 @ 1/8